



## GGG50 GGG40 Cast Ductile Iron Swing Check Valves With Arm Lever Weight

Our Product Introduction

### Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-CV-W-06
- Minimum Order Quantity: 10PCS
- Price: USD2-USD20000 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



### Product Specification

- Highlight: GGG40 ductile iron swing check valve,  
GGG50 ductile iron swing check valve,  
GGG50 ductile iron check valves



### More Images



for more products please visit us on [piping-industry.com](http://piping-industry.com)

## Product Description

### Iron Swing Check Valves Model No. CV-W-06

China ductile iron swing check valve manufacture supply GGG50/GG25 disc check valves with lever weight, DIN PN16.  
Temperature: -30 ~+350

Request a quote

#### Tags:

Cast iron check valve  
Ductile iron check valve  
Bronze seat check valve  
Metal seat check valve  
Flanged check valve  
Swing check valve  
Disc check valve  
Project check valve  
Industry PN16 check valve  
Check valve with lever weight

#### Quick Detail

BC bonnet cover Check Valve

Material	Iron
Design standard	DIN 3202 F6
Body material	Cast iron GG25
Nominal diameter	6" DN150
Pressure	PN16
End connection	RF. Flange EN1092-1
Face to face	DIN3202 F6 EN558-1 Series 48
Working temperature	-30 ~+350
Test and inspection	API 598
Connection	Flange ends conform to ASME B16.5 EN1092-1
Epoxy powder coated inside and outside	250Microns
FBE surface	250Mincrons

#### Product Range

Available Body Material: Cast Iron GG25, Ductile iron GGG40, GGG50  
Available Disc Material: Ductile iron, Bronze  
Optional Seat Ring: Brass, Bronze, SS304, SS316, EPDM  
Optional Design: DIN /BS/ ANSI with difference Face to face length  
Optional Ends: BS4504/EN1092-1 PN16/ ANSI B16.5 RF  
Size Range: DN50-DN600 (2"-24")  
Pressure Range: PN10, PN16, PN20(150LBS)  
Optional surface color: RAL5002, RAL5015. RAL5005, red, black. Or customized

#### Performance

- 1.Iron Body with welded bronze seat ring.
- 2.Clear full opening waterway when disc is in fully open position.
- 3.Operating parts accessible through top opening.
- 4.Bronze bearings support stainless steel hinge pin and pressure sealed with O-rings.
- 5.Heavy ductile iron clapper arm.
- 6.Weights or spring lever may be used on either side for these types of check valves.
- 7.Heavy bronze disc stud is used on all types.
- 8.Iron discs for metal seated valves have bronze disc rings threaded into place.
- 9.Epoxy coated interior and exterior for corrosion resistance.

#### Application:

Pipeline for water, sewage, construction, petroleum, chemical, food, medicine, textile, power, shipbuilding, metallurgy and energy system



+8613292824811



[sales@deyepiping.com](mailto:sales@deyepiping.com)



[piping-industry.com](http://piping-industry.com)

No. 368 Youyi St. Shijiazhuang, Hebei, China